SELF-CONTAINED ICE MACHINE WITH BUILT-IN STORAGE BIN

ICETRO

ICI-120VAD(H)L



W x D x H inch(mm)

26"(660) x 28"(694) x 44.9"(1,141)

Feature

- 262 lbs(119 kg) daily Ice production / 133 lbs(60 kg) Ice storage capacity
- Front Ventilation of Front in / Front out Air flow: Space saving solution with Built-in type
- Simple & Easy to access Front Air filter for cleaning and maintenance
- Designed for easy installation and service
- Easy maintenance by quick disassembling
- Power switch accessible without panel removal
- Simple control, convenient, reliable and long lasting
- Easily access stored ice through slope slide door
- Easy to check Power/Full Ice/ Error with Display Lamp
- High reliability and low maintenance expense
- High density urethane foaming insulation keeps higher rigidity of the ice
- Includes ice scoop, 6" adjustable legs and 10ft power cable
- 304 Durable Stainless steel Construction
- Two ice sizes to choose from Dice and Half Dice
- R-404A Refrigerant


Dimensions

Dimensions	Net	Gross
Width	26"(660 mm)	29"(743 mm)
Depth	28"(694 mm)	30"(774 mm)
Height	44.9"(1,141 mm)	47"(1,188 mm)
Weight	172 lbs(78 kg)	190 lbs(86 kg)


Operating Limits

Ambient Temp Range	10 ~ 38 ℃ (50 ~ 100 ℉)
Water Temp Range	10 ~ 32 ℃ (50 ~ 90 ℉)
Water Pressure	20 ~ 80 psi (1.38 ~ 5.52 bar)
Voltage Range	±10% from regular voltage

Ice Dimension



DICE
22 x 22 x 22 (mm)
⅞ x ⅞ x ⅞ (inch)



HALF DICE
9.5 x 29 x 22 (mm)
⅜ x 1⅛ x ⅞ (inch)


Certification

CE NSF ETL Intertek ETL Intertek UL LISTED KC ISO 9001 SASO

ICETRO
7, GEOMDAN-RO 54BEON-GIL, SEO-GU, INCHEON, KOREA
• TEL : +82-32-814-2160 Ext. 210, 220 • FAX : +82-32-814-1798
• WEB : www.icetro.com • E-mail : sales@icemaker.co.kr

SELF-CONTAINED ICE MACHINE WITH BUILT-IN STORAGE BIN


Dimension – Unit : mm (inch)




Specification

Model	Condenser	Ice Type	Ice Production 24 Hours		Power Consumption	Electrical Option
			Air/Water 21℃(70˚F)/10℃(50˚F)	Air/Water 32℃(90˚F)/21℃(70˚F)		
ICI-120VADL	Air-Cooled	DICE	262 lbs(119 kg)	196 lbs(89 kg)	670 W(±10 %)	208~230V/60Hz/1PH 220~240V/50Hz/1PH
ICI-120VAHL		HALF DICE				


Detail View



Easily access to remove Air filter of Sliding type on the front



Easy maintenance by taking out the whole body



Front inlet/outlet with built-in construction enables optimal space utilization.

※ Design and Specification are subject to change without notice.

ICETRO

7, GEOMDAN-RO 54BEON-GIL, SEO-GU, INCHEON, KOREA
• TEL : +82-32-814-2160 Ext. 210, 220 • FAX : +82-32-814-1798
• WEB : www.icetro.com • E-mail : sales@icemaker.co.kr